

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Issue date: 08/07/2015 Revision date: 03/02/2022 Supersedes version of: 17/11/2020 Version: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	
Product name	
UFI	
Product code	

: Mixture : Cellulose Thinners

: 8K20-20CJ-T00E-8X63

: CETHGEN

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture

: Professional use,Consumer use: Wood Treatment

1.2.2. Uses advised against

No additional information available

Manufacturer J.V. Barrett & Co. Ltd Ltd St Ivel Way Warmley	EU Barrettine (Europe) Ltd Ltd Unit 3D North Point House, North Point Business Park, New Mallow Road
United Kingdom– BS30 8TY Bristol	Ireland– T23 AT2P Cork
United Kingdom	Ireland
T +44 (0)1179 60 00 60	T +44 1179 60 00 60
sales@barrettine.co.uk - www.barrettine.co.uk	sales@barrettine.co.uk - www.barrettine.co.uk

1.4. Emergency telephone number

Emergency number

: +44 (0) 1179 600060 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm Fri.) +44 (0) 1270 502891 (Out of hours emergency number)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

H225
H312
H332
H315

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Specific target organ toxicity — Single exposure, Category 3, NarcosisH336Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritationH335Specific target organ toxicity — Repeated exposure, Category 2H373	Serious eye damage/eye irritation, Category 2	H319
tract irritation	Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2 H373		H335
	Specific target organ toxicity — Repeated exposure, Category 2	H373

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful in contact with skin. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	
	GHS02 GHS07 GHS08
Signal word (CLP)	: Danger
Contains	: Acetone, n-butyl acetate
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour.
	H312+H332 - Harmful in contact with skin or if inhaled.
	H315 - Causes skin irritation.
	H319 - Causes serious eye irritation.
	H335 - May cause respiratory irritation.
	H336 - May cause drowsiness or dizziness.
	H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand.
	P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
	P261 - Avoid breathing fume, mist, vapours, spray.
	P271 - Use only outdoors or in a well-ventilated area.
	P321 - Specific treatment (see supplemental first aid instruction on this label).
	P405 - Store locked up.
	P501 - Dispose of container, contents to a hazardous or special waste collection point.
Child-resistant fastening	: Not applicable
Tactile warning	: Applicable
2.3. Other hazards	

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

3.2. Mixtures			
Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Acetone substance with a Community workplace exposure limit	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330- 49	≥ 30 – < 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Xylene substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	≥ 10	Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
n-butyl acetate substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493- 29	≥ 10 – < 30	Flam. Liq. 3, H226 STOT SE 3, H336
propylene glycol methyl ether acetate substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791- 29	≥5-<10	Flam. Liq. 3, H226
ethylbenzene substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370- 35	< 10	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
DAA; diacetone alcool	CAS-No.: 123-42-2 EC-No.: 204-626-7 EC Index-No.: 603-016-00-1 REACH-no: 01-2119473975- 21	≥1-<3	Eye Irrit. 2, H319
Toluene substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310- 51	< 1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
	CAS-No.: 123-42-2 EC-No.: 204-626-7 EC Index-No.: 603-016-00-1 REACH-no: 01-2119473975- 21	(10 ≤C ≤ 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation	 Call a poison center or a doctor if you feel unwell. Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/effects Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact	 May cause drowsiness or dizziness. May cause respiratory irritation. Irritation. Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Hazardous decomposition products in case of fire	Highly flammable liquid and vapour.Toxic fumes may be released.	
5.3. Advice for firefighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective	equipment and emergency procedures	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe fume, mist, vapours, spray. Avoid contact with skin, eyes and clothing.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for contain	nment and cleaning up	
For containment	: Collect spillage.	
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.	
Other information	: Dispose of materials or solid residues at an authorised site.	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling Hygiene measures	 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe fume, mist, vapours, spray. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	any incompatibilities
Technical measures Storage conditions	Ground/bond container and receiving equipment.Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Acetone (67-64-1)	
Ireland - Occupational Exposure Limits	
Local name	Acetone
OEL TWA [1]	1210 mg/m³
OEL TWA [2]	500 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Acetone
BLV	50 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift - Notations: Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Acetone
WEL TWA (OEL TWA) [1]	1210 mg/m³
WEL TWA (OEL TWA) [2]	500 ppm
WEL STEL (OEL STEL)	3620 mg/m³
WEL STEL (OEL STEL) [ppm]	1500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Safety Data Sheet

Initial - Occupational Exposure Limits Local name 2-Methoxy-1-methylethylacetate OEL TWA [1] 275 mg/m² OEL TWA [2] 50 ppm OEL STEL (ppm) 100 ppm Remark SK (Subtances which have the capacity to penetrate initial skin when they come in a contact with it, and be absorbed into the body), IOELV (indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limit Values) Intel Methoxypropyl acetate WEL TWA (OEL TWA) [1] 274 mg/m² WEL TWA (OEL TWA) [2] 50 ppm WEL STEL (oEL STEL) 648 mg/m² WEL STEL (oEL STEL) [ppm] 100 ppm Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH402005 (Fourth edition, 2020) HSE DAA; diacetone alcol (123-42-2) Initial Agents Code of Practice 2021 Local name Diacetone alcoln (14Hydroxy-4-methyl-pertan-2-one] OEL TWA [1] 240 mg/m² OEL TWA [1] 240 mg/m² OEL TWA [1] 241 mg/m² VEL TWA (OEL T	propylene glycol methyl ether acetate (108-6	5-6)
Local name 2-Methoxy-1-methylethylacelate QEL TWA [1] 275 mg/m² QEL TWA [2] 500 pg/m² QEL STEL [000] 500 mg/m² QEL STEL [000] 100 pgm Remark Sk (Substances which have the capacity to penetrate infact skin when they come in contact whit it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Vances) Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limit Indibotypropyl acalale WEL TWA (OEL TWA) [1] 274 mg/m² WEL TWA (OEL TWA) [2] 50 ppm WEL TWA (OEL TWA) [2] 548 mg/m² WEL TWA (OEL TWA) [2] 549 mg/m² Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference Diacetone alcohl [41+lydrox-4-methyl-pentan-2-one] OLC TWA [2] 50 ppm OLC TWA [2] 50 ppm <tr< td=""><td></td><td>•</td></tr<>		•
OEL TWA [2]60 ppmOEL STEL500 mg/m²OEL STEL (ppm)100 ppmRemarkSK Substances which have the capacity to penetrals intact skin when they come in scrutask with it, and be absorbed into the body.) IOELV (indicative Occupational Exposure Limit Values)Regulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsScruta Minit, and be absorbed into the body.) IOELV (indicative Occupational Exposure Limit Values)WEL TWA (OEL TWA) [1]274 mg/m²WEL STEL (DEL STEL)648 mg/m²WEL STEL (DEL STEL)648 mg/m²Regulatory referenceFeld02005 (Fourth edition, 2020, HSEDAC: discottom alcol (123-42-2)Feld02005 (Fourth edition, 2020, HSETeland - Occupational Exposure LimitsFeld02005 (Fourth edition, 2020, HSELecan nameDiscotore alcohol (4+Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]240 mg/m²Quel tory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsFeld02005 (Fourth edition, 2020), HSELecan nameAl-Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]241 mg/m²Quel tory referenceSer pg/m²United Kingdom - Occupational Exposure LimitsLicad nameAl-Hydroxy-4-methyl-pentan-2-one]WEL TWA (DEL TWA) [1]241 mg/m²WEL TWA (DEL TWA) [1]282 mg/m²WE		2-Methoxy-1-methylethylacetate
OEL STEL 660 mg/m² OEL STEL (ppm) 100 ppm Remark Sk (Substances which have the capacity to penetrate infact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Introducts) Regulatory reference Chemical Agents Occupational Exposure Introducts) United Kingdom - Occupational Exposure Introducts 1-Methoxypropyl acetate Cocia name 1-Methoxypropyl acetate WEL TWA (OEL TWA) [2] 50 ppm WEL STEL (OEL STEL) 50 ppm WEL STEL (OEL STEL) 50 ppm Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference H40/2005 (Fourth edition. 2020). HSE DAL, diacetone alcool (123-42-2) International Exposure Limits Cocia name Ioacanna alcoola [4Hydroxy-4-methyl-pentan-2-one] OEL TWA [2] 60 ppm Cola name Ioacanna alcoola [4Hydroxy-4-methyl-pentan-2-one] OEL TWA [2] 60 ppm Cola name J4Hydroxy-4-methylpentan-2-one] OEL TWA [2] 60 ppm WEL TWA (OEL TWA) [2] 60 ppm	OEL TWA [1]	275 mg/m³
OELSTEL[ppm] 100 pm Remark Sk (Substances which have the capacity to penetrate intact skin when they come in contract with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Indetoxypropyl acetate Local name 1-Methoxypropyl acetate WEL TWA (OEL TWA) [2] 50 pp m WEL STEL (OEL STEL) 548 mg/m ² WEL STEL (OEL STEL) (ppm] 100 pp m Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH402005 (Fourth edition, 2020). HSE DAA; dicactone alcool (123-42-2) Etrand - Occupational Exposure Limits Local name Diactone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [2] 50 pp m Regulatory reference Diactone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [2] 50 pp m Regulatory reference Si pp m Cacil name Hydroxy-4-methylpentan-2-one] OEL TWA [2] Si pp m Regulatory reference Si p	OEL TWA [2]	50 ppm
Remark Sk (Substances which have the capacity to penetrate intact skin when they come in canctar with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values) Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Indehoxypropyl acetate Vent AQ (EL TWA) [1] 274 mg/m ² WEL TWA (OEL TWA) [2] 549 mg/m ² WEL STEL (OEL STEL) 548 mg/m ² WEL STEL (OEL STEL) 548 mg/m ² Regulatory reference 548 ng/m ² Data: clatectone alcohol (123-42-2) 100 ppm Regulatory reference Diactone alcohol [4-Hydroxy-4-methyl-pentan-2-one] Octa name 1040/005 (Fourth edition, 2020). HSE Cel TWA [1] 640 mg/m ³ OEL TWA [2] 60 ppm Regulatory reference Diactone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [2] 60 ppm Regulatory reference 4Hydroxy-4-methylpentan-2-one WEL TWA (0EL TWA) [1] 60 ppm WEL	OEL STEL	550 mg/m ³
contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)Regulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure Limits274 mg/m²Local name1-Methoxypropyl acetateWEL TWA (OEL TWA) [1]274 mg/m²WEL TWA (OEL STEL)50 ppmWEL STEL (OEL STEL)548 mg/m²WEL STEL (OEL STEL) (ppm]546 mg/m²Remark8(Can be absorbed through the skin. The assigned substances are those for which are concerns that dermal absorption will lead to systemic toxicity)Regulatory referenceEH40/2005 (Fourth edition, 2020). HSEDAA; diacetone alcool (123-42-2)Image in the image in	OEL STEL [ppm]	100 ppm
United Kingdom - Occupational Exposure Limits Indehoxypropyl acetate Local name 1-Methoxypropyl acetate WEL TWA (OEL TWA) [1] 274 mg/m³ WEL TWA (OEL TWA) [2] 50 ppm WEL STEL (OEL STEL) 548 mg/m³ WEL STEL (OEL STEL) (ppm] 100 ppm Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE DAA; diacetone alcool (123-42-2) Endendo absorption will lead to systemic toxicity) Ireland - Occupational Exposure Limits Diacetone alcohol [4-Hydroxy-4-methylpentan-2-one] OEL TWA [2] 50 ppm Regulatory reference Chemical Agents Code of Practice 2021 OLE TWA [2] 50 ppm Regulatory reference 4-Hydroxy-4-methylpentan-2-one] United Kingdom - Occupational Exposure Limits Eccl name Local name 4-Hydroxy-4-methylpentan-2-one WEL TWA (OEL TWA) [2] 50 ppm WEL TWA (OEL TWA) [2] 50 ppm WEL STEL (DEL STEL) [pm] 32 mg/m³ WEL STEL (DEL STEL) [pm] 50 ppm	Remark	contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure
Local name1-Methoxypropil acetateWEL TWA (OEL TWA) [1]274 mg/m²WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)548 mg/m²WEL STEL (OEL STEL) (ppm]100 ppmRemarkSk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity)Regulatory referenceE140/2005 (Fourth edition, 2020). HSEDA; diacetone alcool (123-42-2)E140/2005 (Fourth edition, 2020). HSEInder of Cocupational Exposure LimitsIacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]40 mg/m²OEL TWA [2]So ppmRegulatory referenceChemical Agents Code of Practice 2021OEL TWA [2]So ppmRegulatory reference4-Hydroxy-4-methylpentan-2-one]OEL TWA [0]So ppmRegulatory referenceSo ppmUnited Kingdom - Occupational Exposure LimitsSo ppmUced name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [2]So ppmWEL TWA (OEL TWA) [2]So ppmWEL STEL (DEL STEL) [ppm]Si 20 mg/m²WEL STEL (DEL STEL) [ppm]Si 20 mg/m²Regulatory referenceHud/2005 (Fourth edition, 2020). HSEnotary referenceHud/2005 (Fourth edition, 2020). HSENet TVA (OEL TWA) [2]Si 20 mg/m²WEL STEL (DEL STEL) [ppm]Si 20 mg/m²Regulatory referenceHud/2005 (Fourth edition, 2020). HSENet TVA (OEL TWA) [2]Si 20 mg/m²Regulatory referenceHud/2005 (Fourth edition, 2020). HSE	Regulatory reference	Chemical Agents Code of Practice 2021
WEL TWA (OEL TWA) [1]274 mg/m²WEL TWA (OEL TWA) [2]50 pmWEL STEL (OEL STEL)548 mg/m²WEL STEL (OEL STEL) [pm]100 pmRemarkSk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity)Regulatory referenceEH40/2005 (Fourth edition, 2020). HSEDAA; diacetone alcool (123-42-2)Image: State Stat	United Kingdom - Occupational Exposure Limits	
WELTWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)648 mg/m²WEL STEL (OEL STEL) [ppm]100 ppmRemarkSk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity)Regulatory referenceEH40/2005 (Fourth edition, 2020). HSEDAA; diacetorne alcool (123-42-2)Trefared - Occupational Exposure LimitsLocal nameOEL TWA [1]Olacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]OEL TWA [2]0 ppmRegulatory referenceOlacetone alcohol gays and algosts Code of Practice 2021United Kingdom - Occupational Exposure LimitsCode nameLocal name4-Hydroxy-4-methyl-pentan-2-one]WEL TWA (OEL TWA) [1]240 mg/m²WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)60 ppmWEL STEL (OEL STEL)61 ppmWEL STEL (OEL STEL)75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSENet STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSENet STEL (OEL STEL) [ppm]75 ppmRegulatory referenceImage: Stemic Stem	Local name	1-Methoxypropyl acetate
WEL STEL (OEL STEL) [ppm]648 mg/m³WEL STEL (OEL STEL) [ppm]100 ppmRemark&k (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity)Regulatory referenceEH40/2005 (Fourth edition, 2020). HSEDAA; diacetone alcool (123-42-2)Ireland - Occupational Exposure LimitsLocal nameDiacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]240 mg/m³OEL TWA [2]60 ppmRegulatory referenceChenical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsLocal name4-Hydroxy-4-methylpentan-2-one]WEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL) [ppm]32 mg/m³Regulatory reference144/2005 (Fourth edition, 2020). HSEPutry acetate (123-86-4)Fuel Concupational Exposure LimitsInclaname- Fuel Concupational Exposure LimitsInclaname- Fuel Concupational Exposure LimitsVEL STEL (OEL STEL) [ppm]75 ppmRegulatory reference- Fuel Concupational Exposure LimitsInclaname- Fuel Concupational Exposure LimitsIn	WEL TWA (OEL TWA) [1]	274 mg/m ³
WEL STEL (OEL STEL) [ppm] 100 ppm Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE DAA; diacetone alcool (123-42-2) Image: Comparison of the dition, 2020). HSE Ireland - Occupational Exposure Limits Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one] Local name Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [1] 240 mg/m ³ OEL TWA [2] 50 ppm Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Image: Code of Practice 2021 Local name 4-Hydroxy-4-methylpentan-2-one WEL TWA (OEL TWA) [1] 241 mg/m ³ WEL STEL (OEL STEL) 362 mg/m ³ WEL STEL (OEL STEL) 362 mg/m ³ WEL STEL (OEL STEL) S0 ppm Regulatory reference EH40/2005 (Fourth edition, 2020). HSE n-butyl acetate (123-86-4) Image: Code of Practee Code O	WEL TWA (OEL TWA) [2]	50 ppm
Remark Sk (Can be absorbed through the skin. The assigned substances are those for which the are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE DAA; diacetone alcool (123-42-2) Image: Comparison of Co	WEL STEL (OEL STEL)	548 mg/m³
are concerns that dermal absorption will lead to systemic toxicity) Regulatory reference EH40/2005 (Fourth edition, 2020). HSE DAA; diacetone alcool (123-42-2) Image: Concerns that dermal absorption will lead to systemic toxicity) Irelant - Occupational Exposure Limits Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one] Col name Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [1] Go ppm Regulatory reference Chemical Agents Code of Practice 2021 Unted Kingdom - Occupational Exposure Limits Code algents Code of Practice 2021 Local name 4-Hydroxy-4-methylpentan-2-one WEL TWA (OEL TWA) [1] Go ppm WEL TWA (OEL TWA) [2] Go ppm WEL TWA (OEL TWA) [2] So ppm WEL STEL (OEL STEL) [ppm] Ge 2007/m Regulatory reference Fopm n-butyl acetate (122-86-4) Fopm reference Fopm Col name n-Bulyl acetate reference Foldown Fourth edition, 2020). HSE reference Fopm Col name n-Bulyl acetate Col name n-Bulyl acetate Col name	WEL STEL (OEL STEL) [ppm]	100 ppm
DAA; diacetone alcool (123-42-2) treland - Occupational Exposure Limits Local name Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one] OEL TWA [1] 240 mg/m³ OEL TWA [2] 50 ppm Regulatory reference Chemical Agents Code of Practice 2021 United Kingdom - Occupational Exposure Limits Chemical Agents Code of Practice 2021 Local name 4Hydroxy-4-methylpentan-2-one WEL TWA (OEL TWA) [1] 241 mg/m³ WEL TWA (OEL TWA) [2] 50 ppm WEL TWA (OEL TWA) [2] 60 ppm WEL STEL (OEL STEL) 362 mg/m³ Regulatory reference EH40/2005 (Fourth edition, 2020). HSE n-butyl acetate (123-86-4) Ference Icoal name n-Butyl acetate OEL TWA [1] 241 mg/m³ Local name n-Butyl acetate OCL TWA [1] Step pm Cocupational Exposure Limits Icoal name Local name n-Butyl acetate OEL TWA [1] 241 mg/m³ OEL TWA [1] 30 ppm OEL TWA [2] 00 ppm OEL TWA [2] 30 ppm	Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Ireland - Occupational Exposure LimitsLocal nameDiacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]240 mg/m³OEL TWA [2]S0 ppmRegulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsLocal nameLocal name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)Img/m³Local namen-Butyl acetateLocal namen-Butyl acetateOEL TWA [1]241 mg/m³Cola namen-Butyl acetateOEL TWA [2]50 ppmLocal namen-Butyl acetateOEL TWA [1]241 mg/m³OEL TWA [1]50 ppmCola namen-Butyl acetateOEL TWA [1]241 mg/m³OEL TWA [1]50 ppmOEL TWA [1]50 ppmOEL TWA [1]50 ppmOEL TWA [2]50 ppm	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Local nameDiacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]OEL TWA [1]240 mg/m³OEL TWA [2]50 pmRegulatory referenceChemical Agents Code of Practice 2021 Unted Kingdom - Occupational Exposure Limits Local name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 pmWEL STEL (OEL STEL)362 mg/m³Regulatory reference1640/205 (Fourth edition, 2020). HSE n-butyl acetate (123-86-4)-Iread - Occupational Exposure Limits Local name-OEL TWA [1]0.Bityl acetateOC TWA [2]0.Bityl acetateOL TWA [2]0.Bityl acetateOL TWA [2]-Out of the edition, 2020). HSEDecl TWA [1]-OL TWA [1]-OL TWA [2]0.Bityl acetateOL TWA [2]0.Bityl acetateOL TWA [2]0.Dipmical ExposureOL TWA [2]0.Dipmica	DAA; diacetone alcool (123-42-2)	
OEL TWA [1]240 mg/m³OEL TWA [2]50 pmRegulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure Limits4.14 gdrxy-4.methylpentan-2-oneLocal name4.14 mg/m³WEL TWA (OEL TWA) [2]50 pmWEL TWA (OEL STEL)62 mg/m³WEL STEL (OEL STEL) [ppm]51 ppmRegulatory referenceH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)	Ireland - Occupational Exposure Limits	
OEL TWA [2]50 ppmRegulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsLocal name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEIn-butyl acetate (123-86-4)	Local name	Diacetone alcohol [4-Hydroxy-4-methyl-pentan-2-one]
Regulatory referenceChemical Agents Code of Practice 2021United Kingdom - Occupational Exposure LimitsLocal name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)	OEL TWA [1]	240 mg/m ³
United Kingdom - Occupational Exposure Limits Local name 4-Hydroxy-4-methylpentan-2-one WEL TWA (OEL TWA) [1] 241 mg/m ³ WEL TWA (OEL TWA) [2] 50 ppm WEL STEL (OEL STEL) 362 mg/m ³ WEL STEL (OEL STEL) [ppm] 75 ppm Regulatory reference EH40/2005 (Fourth edition, 2020). HSE n-butyl acetate (123-86-4) Image: Marcine Stepsone Limits Local name n-Butyl acetate OEL TWA [1] 241 mg/m ³ OEL TWA [2] 50 ppm OEL TWA [2] 50 ppm	OEL TWA [2]	50 ppm
Local name4-Hydroxy-4-methylpentan-2-oneWEL TWA (OEL TWA) [1]41 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]5 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)	Regulatory reference	Chemical Agents Code of Practice 2021
WEL TWA (OEL TWA) [1]241 mg/m³WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)Ireland - Occupational Exposure LimitsLocal namen-Butyl acetateOEL TWA [1]241 mg/m³OEL TWA [2]50 ppmOEL TWA [2]50 ppm	United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [2]50 ppmWEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)Ireland - Occupational Exposure LimitsIcoal namen-Butyl acetateOEL TWA [1]241 mg/m³OEL TWA [2]50 ppmOEL STEL50 ppm	Local name	4-Hydroxy-4-methylpentan-2-one
WEL STEL (OEL STEL)362 mg/m³WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)Image: Comparison of the test of test	WEL TWA (OEL TWA) [1]	241 mg/m ³
WEL STEL (OEL STEL) [ppm]75 ppmRegulatory referenceEH40/2005 (Fourth edition, 2020). HSEn-butyl acetate (123-86-4)Image: Comparison of the state of	WEL TWA (OEL TWA) [2]	50 ppm
Regulatory reference EH40/2005 (Fourth edition, 2020). HSE n-butyl acetate (123-86-4) Image: Comparise of the edition of	WEL STEL (OEL STEL)	362 mg/m³
n-butyl acetate (123-86-4) Ireland - Occupational Exposure Limits Local name n-Butyl acetate OEL TWA [1] 241 mg/m³ OEL TWA [2] 50 ppm OEL STEL 723 mg/m³	WEL STEL (OEL STEL) [ppm]	75 ppm
Ireland - Occupational Exposure Limits Local name n-Butyl acetate OEL TWA [1] 241 mg/m³ OEL TWA [2] 50 ppm OEL STEL 723 mg/m³	Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Local namen-Butyl acetateOEL TWA [1]241 mg/m³OEL TWA [2]50 ppmOEL STEL723 mg/m³	n-butyl acetate (123-86-4)	
OEL TWA [1] 241 mg/m³ OEL TWA [2] 50 ppm OEL STEL 723 mg/m³	Ireland - Occupational Exposure Limits	
OEL TWA [2] 50 ppm OEL STEL 723 mg/m³	Local name	n-Butyl acetate
OEL STEL 723 mg/m ³	OEL TWA [1]	241 mg/m³
	OEL TWA [2]	50 ppm
OEL STEL [ppm] 150 ppm	OEL STEL	723 mg/m³
	OEL STEL [ppm]	150 ppm
Remark IOELV (Indicative Occupational Exposure Limit Values)	Remark	IOELV (Indicative Occupational Exposure Limit Values)

Safety Data Sheet

n-butyl acetate (123-86-4)	
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Butyl acetate
WEL TWA (OEL TWA) [1]	724 mg/m³
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	966 mg/m³
WEL STEL (OEL STEL) [ppm]	200 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Xylene (1330-20-7)	
Ireland - Occupational Exposure Limits	
Local name	Xylene, mixed isomers
OEL TWA [1]	221 mg/m ³
OEL TWA [2]	50 ppm
OEL STEL	442 mg/m ³
OEL STEL [ppm]	100 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Xylene
BLV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Safety Data Sheet

ethylbenzene (100-41-4)	
Ireland - Occupational Exposure Limits	
Local name	Ethylbenzene
OEL TWA [1]	442 mg/m ³
OEL TWA [2]	100 ppm
OEL STEL	884 mg/m ³
OEL STEL [ppm]	200 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Ethyl benzene
BLV	0.7 g/g creatinine Parameter: mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift at end of workweek - Notations: Ns (Non-specific), Sq (Semi- quantitative) Parameter: ethylbenzene - Medium: end-exhaled air - Sampling time: Not critical - Notations: Sq (Semi-quantitative)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m ³
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	552 mg/m³
WEL STEL (OEL STEL) [ppm]	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Toluene (108-88-3)	
Ireland - Occupational Exposure Limits	
Local name	Toluene
OEL TWA [1]	192 mg/m³
OEL TWA [2]	50 ppm
OEL STEL	384 mg/m³
OEL STEL [ppm]	100 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Toluene (108-88-3)	
BLV	 0.02 mg/l Parameter: toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: toluene - Medium: urine - Sampling time: End of shift 0.3 mg/g creatinine Parameter: o-cresol - Medium: urine - Sampling time: End of shift - Notations: B (Background)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Toluene
WEL TWA (OEL TWA) [1]	191 mg/m³
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Colour Odour Odour threshold pH Relative evaporation rate (butylacetate=1) Melting point Freezing point Boiling point Flash point Auto-ignition temperature Decomposition temperature Flammability (solid, gas) Vapour pressure Relative vapour density at 20 °C Relative density Solubility Partition coefficient n-octanol/water (Log Pow) Viscosity, kinematic	 Liquid Colourless. characteristic. No data available -3 °C No data available So data available No data available
Solubility	Slightly soluble in: Water.No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Safety Data Sheet

SECTION 11: Toxicological infor	
11.1 Information on toxicological effe	ects
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classified : Harmful in contact with skin. : Harmful if inhaled.
Cellulose Thinners	
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (dust,mist)	1.5 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
LC50 Inhalation - Rat (Vapours)	76 mg/l Source: ECHA
propylene glycol methyl ether aceta	te (108-65-6)
LD50 oral rat	8532 mg/kg Source: International Uniform ChemicaL Information Database
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg Source: International Uniform ChemicaL Information Database
DAA; diacetone alcool (123-42-2)	
LD50 oral rat	3002 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity 95% CL: 2738 - 3290
LD50 dermal rat	> 1875 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 1875 mg/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	≥ 7.6 mg/l Source: ECHA
n-butyl acetate (123-86-4)	
LD50 oral rat	12.2 ml/kg Source: ECHA
LC50 Inhalation - Rat (Vapours)	> 4.9 mg/l Source: ECHA
Xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg Source: ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg Source: ECHA, HSDB
LD50 dermal rabbit	15400 mg/kg Source: ECHA, ChemIDPLUS
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77
LC50 Inhalation - Rat (Vapours)	> 20 mg/l Source: ECHA
Skin corrosion/irritation	: Causes skin irritation.

Safety Data Sheet

55(7)	
1 ,	Not classified
	: Not classified
Xylene (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	Not classified
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
DAA; diacetone alcool (123-42-2)	
NOAEL (animal/male, F1)	≈ 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
NOAEL (animal/female, F1)	≈ 600 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
propylene glycol methyl ether acetate (108-6	55-6)
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
DAA; diacetone alcool (123-42-2)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	≥ 4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90- Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information	
12.1. Toxicity	
Hazardous to the aquatic environment, short-term : (acute)	Toxic to aquatic life with long lasting effects. Not classified Not classified
Acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l Source: ECHA
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
propylene glycol methyl ether acetate (108-65	-6)
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
DAA; diacetone alcool (123-42-2)	
LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 - Crustacea [1]	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	> 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-butyl acetate (123-86-4)	
LC50 - Fish [1]	18 mg/l Test organisms (species): Pimephales promelas

EC50 - Crustacea [1]

44 mg/l Test organisms (species): Daphnia sp.

Safety Data Sheet

n-butyl acetate (123-86-4)	
EC50 72h - Algae [1]	674.7 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	23 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7.7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
propylene glycol methyl ether acetate (108-65-6)
Partition coefficient n-octanol/water (Log Pow)	0.43 Source: International Uniform ChemicaL Information Database
DAA; diacetone alcool (123-42-2)	
Partition coefficient n-octanol/water (Log Pow)	0.445 Source: ECHA
n-butyl acetate (123-86-4)	
Partition coefficient n-octanol/water (Log Pow)	1.78 Source: HSDB
Xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ethylbenzene (100-41-4)			
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB		
Toluene (108-88-3)	Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow) 2.73 Source: HSDB			
12.4. Mobility in soil			
Xylene (1330-20-7)			
Mobility in soil 537 Source: ECHA			
12.5. Results of PBT and vPvB assessment			
No additional information available			

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations 13.1. Waste treatment methods Waste treatment methods Additional information : Dispose of contents/container in accordance with licensed collector's sorting instructions. : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shippin	g name			
FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate)	Flammable liquid, n.o.s. (Xylene ; Acetone ; n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate)	FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate)
Transport document descr	iption			
UN 1993 FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate), 3, II, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate), 3, II	UN 1993 Flammable liquid, n.o.s. (Xylene ; Acetone ; n- butyl acetate), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Xylene ; Acetone ; n-butyl acetate), 3, II
14.3. Transport hazard o	class(es)			
3	3	3	3	3
3				
14.4. Packing group				
II	II	II	II	II

Safety Data Sheet

ADR	IMDG	ΙΑΤΑ	ADN	RID		
14.5. Environmental haza			AUN	שוא		
		Dangaraus for the	Dongorous for the	Daparaus for the		
Dangerous for the environment: No						
	Marine pollutant: No					
No supplementary information	n available					
14.6. Special precautions	for user					
Overland transport						
Classification code (ADR)	: F1					
Special provisions (ADR)		4, 601, 640C				
imited quantities (ADR)	: 11					
Excepted quantities (ADR)	: E2					
Packing instructions (ADR)	: P0	01				
Vixed packing provisions (ADF		19				
Portable tank and bulk contain						
Portable tank and bulk contain	er special provisions : TP	1, TP8, TP28				
(ADR)						
Tank code (ADR)	: L1.	5BN				
Vehicle for tank carriage	: FL					
Transport category (ADR)	: 2					
Special provisions for carriage	- Operation (ADR) : S2	S20				
Hazard identification number (Kemler No.) : 33					
Orange plates	: 🗖	22				
	-	33 1993				
Tunnel restriction code (ADR)	: D/E					
EAC code	: •3)					
Transport by sea						
Special provisions (IMDG)	: 274	1				
Limited quantities (IMDG)	: 1L					
Excepted quantities (IMDG)	: E2					
Packing instructions (IMDG)	: P0	01				
BC packing instructions (IMD						
Tank instructions (IMDG)	: T7					
Tank special provisions (IMDG		1, TP28, TP8				
EmS-No. (Fire)	; F-E					
EmS-No. (Spillage)	: S-E					
Stowage category (IMDG)	: B					
Air transport						
PCA Excepted quantities (IAT)	A) : E2					
PCA Limited quantities (IATA)	; Y3					
PCA limited quantity max net c						
PCA packing instructions (IAT)		3				
PCA max net quantity (IATA)	: 5L					
CAO packing instructions (IAT		1				
CAO max net quantity (IATA)	: 601					
Special provisions (IATA)		: A3				
ERG code (IATA)	: 3H					
nland waterway transport						
Classification code (ADN)	: F1					
Special provisions (ADN)		4, 601, 640C				
_imited quantities (ADN)	: 1L					
Excepted quantities (ADN)	: E2					
Equipment required (ADN)		, EX, A				
	. 77	, LA, A				

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ventilation (ADN) Number of blue cones/lights (ADN)	-	VE01 1
Rail transport Classification code (RID) Special provisions (RID) Limited quantities (RID) Excepted quantities (RID) Packing instructions (RID) Mixed packing provisions (RID) Portable tank and bulk container instructions (RID) Portable tank and bulk container special provisions (RID) Tank codes for RID tanks (RID) Transport category (RID)		F1 274, 601, 640C 1L E2 P001 MP19 T7 TP1, TP8, TP28 L1.5BN 2
Colis express (express parcels) (RID) Hazard identification number (RID)	:	CE7 33

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Substances subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 july 2012 concerning the export and import of hazardous chemicals: Acetone (67-64-1)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf Contains substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes:

New format.

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes version of	Modified	
	Revision date	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Hazard pictograms (CLP)	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
6.3	For containment	Added	
8.2	Hand protection	Modified	
11.1	ATE CLP (dust,mist)	Modified	
12.1	Ecology - general	Modified	
16	Abbreviations and acronyms	Modified	

Abbreviations and act	ronyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Abbreviations and	acronyms:
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Full text of H- and EO	-statements.
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
STOT RE 2 Specific target organ toxicity — Repeated exposure, Category 2	
STOT SE 3 Specific target organ toxicity — Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.